

DATE: 10/13/2011
CHECKED BY: J.E.
TOWN OF BETHEM
COUNTY OF ALBANY
STATE OF NEW YORK

SCALE: AS NOTED
SHEET 1 OF 1

LANDS OF WINDSOR DEVELOPMENT
NEW SCOTLAND ROAD
TOWN OF BETHEM
COUNTY OF ALBANY
STATE OF NEW YORK

ingalls & associates, llp
REGISTERED PROFESSIONAL ENGINEERS
REGISTERED PROFESSIONAL SURVEYORS
100 WEST 10TH STREET
ALBANY, NY 12206
TEL: (518) 938-3333
FAX: (518) 938-3333

STATE OF NEW YORK
COUNTY OF ALBANY
TOWN OF BETHEM

ingalls & associates, llp
REGISTERED PROFESSIONAL ENGINEERS
REGISTERED PROFESSIONAL SURVEYORS
100 WEST 10TH STREET
ALBANY, NY 12206
TEL: (518) 938-3333
FAX: (518) 938-3333

NO. DATE
1 02/27/12
2 02/27/12

REVISIONS
1. REVISIONS
2. REVISIONS

NOTE: 48 HOURS PRIOR TO ANY CONSTRUCTION ACTIVITIES, THE CONTRACTOR SHALL CONTACT UNDERGROUND UTILITIES, 1-800-952-7962. ALL SAFETY NEW YORK TO LOCATE ALL UTILITIES PRIOR TO ANY CONSTRUCTION ACTIVITIES.

TOWN ROAD WITHIN NEW SCOTLAND ROAD R.O.W.
STA: 10+17 TO 10+64
TYPICAL SECTION
NOT TO SCALE

Diagram showing a typical cross-section of a road. The road width is 11' minimum. The crown is 12" minimum. The elevations are 12' ITEM 304.02, 11' ITEM 304.02, 10' ITEM 304.02, 9' ITEM 304.02, 8' ITEM 304.02, 7' ITEM 304.02, 6' ITEM 304.02, 5' ITEM 304.02, 4' ITEM 304.02, 3' ITEM 304.02, 2' ITEM 304.02, 1' ITEM 304.02.

PIPE CASING DETAIL FOR
DIRECTIONAL SEWERLINE BORING
NOT TO SCALE

Diagram showing a cross-section of a pipe casing. The casing is 24" steel. The pipe is 24" diameter. The casing is 24" thick. The pipe is 24" diameter. The casing is 24" thick. The pipe is 24" diameter. The casing is 24" thick.

- 1. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS LESS THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 2. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 3. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 4. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 5. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 6. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 7. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.
- 8. WHEN THE MAXIMUM LINE WIDTH OF THE ROADWAY IS GREATER THAN 10' THE ROADWAY SHALL BE CLOSED FOR A MINIMUM OF 10'.

SHORT OR INTERMEDIATE TERM STATIONARY
LANE CLOSURE ON 2-LANE 2-WAY ROADWAY
(NOT TO SCALE)

Diagram showing a lane closure on a 2-lane 2-way roadway. The road is 24' wide. The lane closure is 12' wide. The road is 24' wide. The lane closure is 12' wide. The road is 24' wide. The lane closure is 12' wide.

LANE CLOSURE ON 2-LANE 2-WAY ROADWAY
SHORT OR INTERMEDIATE TERM STATIONARY
(NOT TO SCALE)

Diagram showing a lane closure on a 2-lane 2-way roadway. The road is 24' wide. The lane closure is 12' wide. The road is 24' wide. The lane closure is 12' wide. The road is 24' wide. The lane closure is 12' wide.

PROPOSED INTERSECTION/SANITARY SEWER CONNECTION PLAN
SCALE: 1"=20'

Diagram showing a proposed intersection of a sanitary sewer line with a road. The road is 24' wide. The sewer line is 24" diameter. The road is 24' wide. The sewer line is 24" diameter. The road is 24' wide. The sewer line is 24" diameter.

PROFILE WITHIN NYSOT R.O.W.
HORIZONTAL SCALE: 1"=30'
VERTICAL SCALE: 1"=3'

Diagram showing a profile of a road within the NYSOT R.O.W. The road is 24' wide. The profile is 12' high. The road is 24' wide. The profile is 12' high. The road is 24' wide. The profile is 12' high.

Map showing the location of the project site. The site is located at the intersection of New Scotland Road and Town Road. The site is located at the intersection of New Scotland Road and Town Road. The site is located at the intersection of New Scotland Road and Town Road.

- 1. MAINTENANCE AND PROTECTION OF TRAFFIC SHALL BE PROVIDED IN ACCORDANCE WITH THE CURRENT EDITION OF THE FEDERAL AID CODE WITH NYS SUPPLEMENT, AND THE CURRENT SET OF NYSOT STANDARD SHEETS.
- 2. THE FINAL RESPONSIBILITY FOR THE PROTECTION OF THE TRAVELING PUBLIC SHALL REST WITH THE CONTRACTOR.
- 3. PRIOR TO THE START OF WORK, THE CONTRACTOR SHALL SUBMIT A PROPOSED PLAN TO THE TRAFFIC CONTROL DIVISION FOR APPROVAL.
- 4. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 5. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 6. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 7. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 8. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 9. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.
- 10. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING SIGNS FOR THE DURATION OF THE PROJECT OR UNTIL NEW REPLACEMENT SIGNS ARE INSTALLED.