

SWPPP (STORMWATER POLLUTION PREVENTION PLAN)
* HAS BEEN DETERMINED TO BE REQUIRED BASED ON SCOPE OF PROJECT. SWPPP REQUIRES DOCUMENTS FROM CONSTRUCTION TEAM.
* HAS BEEN DETERMINED NOT TO BE REQUIRED BASED ON SCOPE OF PROJECT.
* REFER TO REQUIREMENTS LISTED ON THIS SHEET AND SPECIFICATION SECTION 01560 ENCLOSED IN THE SWPPP. IF SCOPE OF PROJECT REQUIRES SWPPP FOR A SWPPP AND NTS/DEC PERMITTING MAY REQUIRE RE-EVALUATION.

GENERAL NOTES
1. FLAG THE GRADING LIMITS AND MARK A 10' BUFFER AREA BEHIND THE GRADING LIMITS FOR PROTECTION.
2. INSTALL TEMPORARY CONSTRUCTION ENTRANCE AT APPROXIMATE 10' BUFFER AREA FROM THE GRADING LIMITS. THE ENTRANCE SHALL BE PLACED.
3. INSTALL PROTECTIVE MEASURES AROUND TREES TO BE RETAINED WITHIN GRADING LIMITS.
4. INSTALL BRIGHTLY COLORED CONSTRUCTION FENCE ALONG ROAD TO LIMIT VEHICULAR ACCESS TO STONE DRIVEWAY OR ACCUMULATIONS.
5. CONSTRUCTION PROTECTIVE MEASURES AT STONE DRIVEWAY OR SLOPE FROM THE SITE THAT ARE VULNERABLE TO SEAMT ACCUMULATIONS.
6. COMPLETE SITE CLEARING, STOCKPILE SAVED MATERIALS IN DESIGNATED AREAS.
7. INSTALL SILT FENCES IN LOCATIONS AROUND THE PERIMETER OF THE PROJECT. THE SILT FENCES SHALL BE A MINIMUM OF 10' BUFFER OF HORIZONTAL DISTANCE OR AS SPECIFIED, MEASURED PERPENDICULAR TO THE SLOPE.
8. INSTALL SILT FENCES, STRAW BALE DIKES, DIVERSION SINKS, STRUCTURED TO EXTENT POSSIBLE WITHIN GRADING LIMITS.
9. CONSTRUCTION PROTECTIVE MEASURES AT STONE DRIVEWAY OR SLOPE FROM THE SITE THAT ARE VULNERABLE TO SEAMT ACCUMULATIONS.
10. ROUTE ALL DRAINAGE AND SUMP PUMP OUTFALLS, OF TURBID QUALITY, DIRECTLY TO SEDIMENT BASINS OR OTHER APPROPRIATE TREATMENT.
11. THE CONTRACTOR SHALL MAINTAIN CONSTRUCTION OF ANY DRAINAGE AREAS AS SOON AS POSSIBLE, BUT IN NO CASE MORE THAN 10 DAYS AFTER INITIAL DISTURBANCE OF THE RESPECTIVE AREAS OF THE PROJECT. THE CONTRACTOR SHALL MAINTAIN THE EARTHWORK AND STABILIZATION WORK PERFORMED. EXCEPTIONS TO THIS POLICY CAN BE GRANTED UNDER NORMAL CONDITIONS IN THE FOLLOWING INSTANCES:
a. WHEN THE CONSTRUCTION ACTIVITY TEMPORARILY BY THE CONTRACTOR IS NECESSARY TO MAINTAIN THE PROJECT.
b. WHERE CONSTRUCTION ACTIVITY ON A PORTION OF THE SITE IS TEMPORARILY CEASED, AND EARTH-STABILIZATION ACTIVITIES ARE INITIATED IMMEDIATELY UPON COMPLETION OF THE TEMPORARY STABILIZATION MEASURES.
c. WHEN THE CONSTRUCTION ACTIVITY TEMPORARILY BY THE CONTRACTOR IS NECESSARY TO MAINTAIN THE PROJECT.
12. ALL EROSION CONTROL MEASURES SHALL REMAIN IN PLACE UNTIL THE PROJECT IS COMPLETE. THE CONTRACTOR SHALL MAINTAIN THE EARTHWORK AND STABILIZATION WORK PERFORMED. EXCEPTIONS TO THIS POLICY CAN BE GRANTED UNDER NORMAL CONDITIONS IN THE FOLLOWING INSTANCES:
a. WHEN THE CONSTRUCTION ACTIVITY TEMPORARILY BY THE CONTRACTOR IS NECESSARY TO MAINTAIN THE PROJECT.
b. WHERE CONSTRUCTION ACTIVITY ON A PORTION OF THE SITE IS TEMPORARILY CEASED, AND EARTH-STABILIZATION ACTIVITIES ARE INITIATED IMMEDIATELY UPON COMPLETION OF THE TEMPORARY STABILIZATION MEASURES.
c. WHEN THE CONSTRUCTION ACTIVITY TEMPORARILY BY THE CONTRACTOR IS NECESSARY TO MAINTAIN THE PROJECT.

SWPPP (STORMWATER POLLUTION PREVENTION PLAN)
DESIGN TABLE
SLOPE (H:V) 1:1 2:1 3:1 4:1 6:1
VERTICAL INTERVAL 3 4 5 6 8
CONSTRUCTION SPECIFICATIONS
1. WILLOW MATS SHALL BE 3" MINIMUM DIAMETER AND BUNDLED WITH TAPERED ENDS TO AN OVERALL LENGTH 18 INCHES LONGER THAN THE STEMS.
2. STRUCTURAL MEASURES SUCH AS REVEGETATION, DRAINAGE, SURFACE DITCHES WILL BE RESTORED TO ORIGINAL CONDITION.
3. ANCHOR STAKES WILL BE PLACED ON THE SLOPE AT THE DESIRED CONTOUR INTERVAL.
4. WORKING FROM THE BOTTOM OF THE SLOPE TO THE TOP, EXCAVATE WATERS TRENCH JUST ABOVE THE STAKES. TRENCH SHALL BE MADE TO THE DEPTH OF THE MATS.
5. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.
6. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.
7. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.
8. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.
9. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.
10. MATS SHALL BE LAYED WITH SOIL LAYING ABOUT 1/2" TO 1" CAPABLE OF WITHSTANDING THE WEIGHT OF THE MATS.

GENERAL NOTES
1. ALL TEMPORARY SWALES SHALL HAVE UNINTERRUPTED POSITIVE GRADE TO AN OUTLET.
2. DIVERTED RUNOFF FROM A DISTURBED AREA SHALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE.
3. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
4. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
5. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
6. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
7. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
8. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
9. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
10. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
11. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
12. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
13. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
14. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
15. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.

GENERAL NOTES
1. ALL TEMPORARY SWALES SHALL HAVE UNINTERRUPTED POSITIVE GRADE TO AN OUTLET.
2. DIVERTED RUNOFF FROM A DISTURBED AREA SHALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE.
3. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
4. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
5. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
6. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
7. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
8. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
9. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
10. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
11. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
12. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
13. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
14. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.
15. SWALES SHALL BE CONSTRUCTED TO MAINTAIN A MINIMUM OF 10' BUFFER AREA FROM THE GRADING LIMITS.